



**We make
highways
talk™**

- **MANAGEMENT**
- **SAFETY**
- **PRESERVATION**

International Road Dynamics Inc. develops and maintains traffic management products and systems technology that make highways talk. What are they saying? They are providing information that roadway administrators need to manage traffic, preserve infrastructure and provide safety warnings to drivers.

IRD's multi-discipline, innovative and customer-focused team is expert in advanced technologies, advanced traffic solutions and custom-designed systems.



TRS Traffic Recording Systems

The TRS product line offers superior data collection capability and flexibility. The standard display is a four line by twenty character LCD. The 16 alphanumeric keys allow the user the option to program the unit without the use of a computer. Depending on the application, the unit can be packaged in three different housings and may be used portably or permanently. Data can be downloaded from the site without interrupting the data collection process.

TRS Rack II



FEATURES

- Up to 24 inputs
- Piezo, tube, loop, contact and environmental
- 20 Character by 4 line display
- Binned and event data
- Portable and permanent housings
- Real-time clock
- Piezo Weigh-In-Motion
- 8 Lanes of Classification
- **Bluetooth®** wireless technology optional



Mini TRS and TRS



TRS

Traffic Recording Systems

The TRS can be operated via the integrated keypad and display or via a serial link with a computer or modem. Upon power up, the TRS is completely menu driven for ease of use in the field. To serve the special needs of many different users, the TRS options include: solar panel, pcmcia interface, expandable memory, environmental sensors and WIM.



Mini TRS Inputs



Display and Keypad

TECHNICAL DATA

Enclosure:	Cast aluminum (powder coat); Sheet metal card cage (TRS)
Time periods:	1 to 60 minute intervals
Data Storage:	64 MB - 16 GB MicroSD
Power:	Typically 45 days per charge; On/Off switch standard
Dimensions:	17.8 cm x 34.3 cm x 15.2 cm (7 in x 13.5 in x 6 in)
Mini:	22.9 cm x 17.8 cm x 12.7 cm (9 in x 7 in x 5 in)
Rack II:	48.3 cm card cage (19 in card cage)
Weight:	Less than 15 lbs
Mini:	Less than 10 lbs
Display:	20 Character by 4 line
Accuracy:	Self adjusting air switches Meets or exceeds TMG and ASTM standards
Communications:	RS232 serial comms from 300 to 115 K baud, USB, optional Bluetooth®

* The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such trademarks by International Road Dynamics Inc. is under license. Other trademarks and trade names are those of their respective owners.



Corporate Office

702 - 43rd Street East
Saskatoon, Saskatchewan
Canada S7K 3T9
Tel: (306) 653-6600
Fax: (306) 242-5599
Toll Free: 1-877-7IRD-ITS (747-3487)
Email: info@irdinc.com

U.S. Office

2402 Spring Ridge Drive, Suite E
Spring Grove, IL
USA 60081
Tel: (815) 675-1430
Fax: (815) 675-1530

Publicly Traded on the TSX (Symbol IRD)
Find out more about IRD on our website: www.irdinc.com

IRD products and components are protected by one or more worldwide patents and/or trademarks.
IRD reserves the right to change, modify, or improve its products at any time without notice.

PRINTED IN CANADA